





SuperMax Lighting

LiquaLED Bullet Lights are SloanLED's latest spa offering for individual points of light. Compatible with most small fiber optic fittings, these bullet-shaped LED modules are pre-wired in a choice of cable sets for easy daisy-chain installation throughout the spa. Utilizing the latest in LED technology, these modules provide full-spectrum color changing, ultra bright light output and unsurpassed efficiency. The perfect complement to the LiquaLED Cluster Main Lights.

- LiquaLED Bullet Lights - New, patent pending "bullet" design LED modules with rugged LED-to-cable connection
- Color Changing LEDs – Latest LED technology produces the full spectrum of colors and allows for color changing and sequencing
- Daisy-Chain Wiring - Flexible configurations and easy installation
- Small Diameter LED Modules - Compatible with most small fiber optic fittings
- Positive Lock Connectors - Quick installs; reliable, industrial strength connections
- Connector Boot - Protection from moisture, dirt and foaming operations
- HighTemp Cable Sets - Proven not to melt under the highest temperature foaming operations
- Patent Pending LED Boot - Vibration proof attachment; no adhesives required
- Efficient Electrical Design - Drives more lights from the same power pack
- Integrated Fuse Protection - No fuss, reliable operation
- Jumpers - In two lengths, with mating connectors and boots
- Accessory Lens – Available UV stable polycarbonate lens and nylon hex nut, fit 3/8" hole; Lens PN 400372; Nut PN 400338; Lens/Nut combo PN 400372-N



Quad-LED Cable Set



Dual-LED Cable Set



Single-LED Cable Set




Accessory Lens & Nut



Bullet LED with Boot



Color Changing LEDs



Waterfall Installation

Item Description	LiquaLED Bullet Lights & Cable Sets			Jumpers	
	Quad-LED Cable Set	Dual-LED Cable Set	Single-LED Cable Set	2' Jumper	5' Jumper
Part Number	701564-4-DL	701564-2-DL	701564-1-DL	410117-24	410117-60
# Modules (Individual Points of Light)	4	2	1	-	-
Typical Maximum Current	80 mA	40 mA	50 mA	-	-
Cable Length (connector-to-connector)	48 inch	48 inch	48 inch	24 inch	60 inch